DATASHEET

Trimble T10 Tablet



HIGH-PERFORMANCE PROCESSING POWER IN THE FIELD

Trimble brings the advantages of fast computing power and a large screen to the field with the Trimble® T10 tablet. The Trimble T10 is a powerful, rugged device created for building construction fieldwork. At the same time it supports demanding desktop applications to provide a single-device solution for efficient data processing on the job.

Designed to work all day even in difficult environments and conditions, the Trimble T10 enables contractors in a variety of applications to efficiently and reliably collect and process data for analysis and visualization on a significantly larger display using the latest Windows® 10 operating system.

FAST AND POWERFUL COMPUTER PROCESSING

The fast and powerful processing engine of the Trimble T10 lets you carry out challenging field applications without difficulty. Rapid processing of points, PDF's and models as well as collected field data ensures the T10 won't slow you down. Save time and money and be more productive by having your field work completed quickly with a high degree of detail, increasing the value of your data.

ENHANCED MODEL VISUALIZATION WITH LARGE SCREEN DISPLAY

Whether performing data collection, field inspections or performing complex layout, the generous 10.1-inch screen that reads in bright sunlight ensures easy viewing of your data. The higher screen resolution offers enhanced model interaction, providing accurate information on which to base informed decisions in the field.

LATEST WINDOWS DESKTOP OPERATING SYSTEM

Make the field your office and enjoy the use of full Windows desktop applications on the Trimble T10 wherever you are. Supporting the Windows 10 operating system, the tablet works well with any modern application you need to get your field tasks completed and processed without using a separate laptop computer or returning to headquarters.

Key Features

- Fast and powerful processing to support demanding field applications and create high-quality deliverables even when outside of the office
- Enhanced interaction with detailed map and imagery through large 10.1-inch, high resolution display
- Full Windows operating system brings office to the field
- Rugged form factor and long battery life for all day field operation even in tough environments

Additionally, for a complete field to office workflow solution, utilize Trimble field and office software such as Trimble Field Link and Trimble Field Link Office to process and manage your data, and create high quality deliverables for your organization—even while in the field.

ALL DAY RUGGED FIELD OPERATION

The Trimble T10 is built tough. Unlike modern consumer-grade tablets, the IP65-rated Trimble T10 with military-grade MIL-STD-810G ruggedness certification will withstand anything the elements throw at you. Protected against rain, mud, dust, sand, and extreme temperatures— as well as drops and shocks your collected data is secure no matter what you encounter. Plus, the hot-swappable long life battery will keep going all day so you can get the job done.

Wherever you go, whatever conditions you face, the powerful and efficient Trimble T10 tablet won't let you down.



Trimble T10 Tablet

Processor Intel® Core™ i7, Clock frequency: 2.5 GHz

User InterfacePower button, RF switch,

Battery 11.4V, 5400 mAh (standard capacity), hot swappable

Battery life (enhanced capacity)>12 hours @ 20° C with GPS on⁴

Operating-20° to +60° C (-4° to 140° F)7

Water & dust proof..... IP65

Vibration / Shock resistanceMIL-STD-810G

EMI / EMC toleranceMIL-STD-461F

Display.....LED backlight scratch-resistant, auto rotate

AudioBuilt-in microphone and speaker

(Wi-Fi only version with standard battery)

Optional detachable full keyboard with trackpad

11.4V. 7980 mAh (enhanced capacity

3 programmable keys

Power / Battery Status LED On screen keyboard

+ + + + + + + + + +

TECHNICAL SPECIFICATIONS

Physical

STANDARD FFATURES

System

- Intel[®] 6th Generation Core[™] i7 processor
- Intel HD Graphics 520
- 8 GB RAM¹
- . 256 GB Storage (4G version: 512 GB)²
- 10.1" LED-backlight screen with 10-point capacitive multi-touch
- Active Pen support .
- . 5 Megapixel rear camera
- High-sensitivity GNSS/SBAS receiver and antenna
- Wi-Fi 802.11ac, 2.4GHz / 5GHz dual-band
- Bluetooth® v 4 0 L F
- 4G radio version available
- User replaceable battery (standard or enhanced capacity), hot swappable
- Integrated speaker and microphone
- NIST (National Institute of Standards and Technology) compliant BIOS .
- TPM (Trusted Platform Module) 2.0 support
- . Rugged ABS + PC plastics and magnesium-aluminum alloy enclosure
- Rubber bumpers on each corner for handling protection
- MIL-STD-810G Shock, Drop and Vibration
- IP65 Dust and Moisture Ingress Protection

Operating System

Microsoft® Windows® 10 IoT Enterprise •

Communications

- Cellular: 4G-LTE, Data only ³
- (Not available on Wi-Fi only version)
- Wi-Fi 802.11ac, 2.4 GHz/ 5GHz dual band
- Bluetooth 4.0 LE
- USB 3.0

Standard Accessories

- Lanvard
- Screen protectors (x2)
- A/C charger

Optional Accessories

- Active pen
- Detachable full keyboard with trackpad (for hybrid 2-in-1)
- Enhanced capacity battery
- Office dock with ethernet and dual-display support
- Pole bracket with cradle

Footnotes

- 1 GB = 1,000,000,000 bytes.
- Total usable memory will be less depending upon actual system configuration.
- Frequencies and channels depending on 4G radio version. Approximate charging time for standard battery. Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other settings or preferences.
- SBAS (Satellite Based Augmentation System), where available.
- 6 Horizontal Root Mean Squared accuracy, Requires reasonable multipath conditions, Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception.
- Tested under MIL-STD-810G method 501.6. Procedure II. and method 502.6. Procedure II. Battery capacity is reduced at lower temperatures or extremely high temperatures. Batteries should neither be charged at temperatures below 32°F (0°C) nor temperatures above 113°F (+45°C) to avoid impacting battery longevity and performance.



21505 Bents Court NE Aurora, OR 97002

503.280.1888

Singapore PTE Limited 3 HarbourFront Place #13-02 HarbourFront Tower Two Singapore 099254 SINGAPORE

Audio jack 3.5 mm

USB 3.0

exposure control

Accelerometer

FUROPE

Trimble Germany GmbH Am Prime Parc 11 65479 Raunheim GERMANY

NORTH AMERICA

Trimble Inc. 10368 Westmoor Drive Westminster CO 80021 USA

BuildingPoint

BuildingPoint Pacific

833 Montague Ave. San Leandro, CĂ 94577

510.618.2550

619.260.1552

San Diego, CA 92121

www.BuildingPointPacific.com

©2019, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and RealWorks are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Lightning is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022519-144 (06/19)

11750 Sorrento Valley Road, Ste. 140

www.trimble.com



ASIA-PACIFIC Trimble Navigation

Real-time SBAS 2-5 m typical

1/0 AC / DC AdapterInput: 100-240V AC, Output: 19V DC, 3.42A Digital camera (outward) 5 MP with auto-focus, white balance, gain control and

Sensors Electronic Compass GNSS

Environmental

Temperature

Input/Output

Dual constellation system GPS/GLONASS or GPS/Beidou Accuracy Specifications (Horizontal RMS)6

Caution: Do not expose bare skin to this product when handling this unit in extreme hot or cold environments. Do not charge batteries in extreme hot environments.

Internal antenna: 72 channelsGPS L1 C/A, GLONASS, Beidou, OZSS, SBAS Integrated real-timeSBAS5 (WAAS/EGNOS/MSAS/GAGAN)